

AX UPE S&D EN12115



Suction and delivery hose of a wide range of aggressive chemicals, petroleums, acids, bases, ketons, esters, aromatic, aliphatic and chlorinated hydrocarbons. Also suitable for animal or vegetable foodstuffs and alcoholic drinks.

- **Tube:** smooth translucent conductive UHMWPE(*) rubber (also available in black), abrasion resistant (FDA standard)
- **Reinforcement:** high strength synthetic cord, embedded steel helix wire and anti-static copper wire to facilitate the electrical connection
- **Cover:** black, anti-static CR with cloth impression ($R < 10^6 \Omega/m$) weathering, ozone resistant

Norm: EN 12115

Temperature range: -30°C up to +90°C
(depending on medium and concentration)

Applications

Feel free to consult us for chemical resistance.

(*) Ultra High Molecular Weight Poly-Ethylene

Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Vacuum	Bending Radius
13 x 25	570	16	64	0,9	170
19 x 31	680	16	64	0,9	190
25 x 37	830	16	64	0,9	225
32 x 44	1.050	16	64	0,9	260
38 x 51	1.300	16	64	0,9	340
51 x 67	2.200	16	64	0,9	410
63,5 x 79	2.600	16	64	0,9	450
76 x 91	3.000	16	64	0,8	525
102 x 118	4.400	16	64	0,8	675
152 x 172	7.800	16	64	0,8	900

Product ID: 40203

Source URL: <http://articom.be/en/products/40000/40200/ax-upe-sd-en12115-0>