

Alfavac PU MH AA



Temperature: -30°C to +100°C

Very flexible and extremely durable polyurethane (PU) hose, that can be used to transport abrasive materials by air and that has a good resistance to hydrolysis and bacteria. Doesn't rip easily and can be earthed by connecting both ends of the steel helix. Resistant to wet, micro-organisms and grass algae.

Construction: 1,4mm transparant PU with an embedded steel helix with white pvc cover.

Remark: Anti algae version

Applications

(industrial) lawn mowers

Reference	Diameter (mm)	Weight (g/m)	Bending radius (mm)	Vacuum (mH2O)	Coil length (m)
VFPUMHAA100	100	1020	300	3,0	10
VFPUMHAA120	120	1220	360	2,5	10
VFPUMHAA125	125	1280	390	2,5	10
VFPUMHAA150	150	1460	450	2,0	10
VFPUMHAA160	160	1580	480	2,0	10
VFPUMHAA180	180	1750	540	1,5	10
VFPUMHAA200	200	1940	600	1,2	10
VFPUMHAA250	250	3150	750	1,0	10
VFPUMHAA300	300	3780	900	0,9	10

Product ID: 14210

Source URL: <http://articom.be/en/products/10000/14000/alfavac-pu-mh-aa-0>