

## AX EPDM S&D EN12115

Suction and delivery hose of highly aggressive chemical products, organic and non organic acids in high concentration, slats, bases, ketones, dye products for cloth industry and also hot water.

- **Tube:** black smooth and anti static EPDM
- **Reinforcement:** high strength synthetic cord plus embedded steel helix wire and anti-static copper wire to facilitate the electrical connection
- **Cover:** black EPDM with cloth impression, anti-static ( $R < 10^6 \Omega/m$ ), weathering, ozone and chemical products resistant

**Norm:** EN 12115

Temperature range depends on medium and concentration.

Cleaning with hot water or steam (120°C)

**Note: NOT suitable for hydrocarbons**

### Applications

Contact us for specific chemical resistance.

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Bending radius (mm)	Coil length (m)
	32 x 42	1.370	10	40	170	40
	38 x 49	1.670	10	40	230	40
	50 x 63	2.220	10	40	310	40
	63 x 77	3.090	10	40	380	40
	75 x 89	3.640	10	40	500	40
	100 x 115	4.790	10	40	700	40

Product ID: 40205

**Source URL:** <http://articom.be/en/products/40000/40200/ax-epdm-sd-en12115-0>