


## UNITRIX 60



The multi purpose hose UNITRIX 60® provides best results when used in the areas of mechanical engineering, farming, forestry, garages, quarries, construction sites, shipbuilding, railway industry, mineral oil, chemical, and petrochemical industry.

Temperature: -25°C to +85°C It can be used with compressors, barrel pumps and aggregates.

- **Inner tube:** black, non-porous smooth NBR lining
- **Reinforcements:** synthetic fibres
- **Cover:** NBR, resistant to oil, grease and chemicals
- **Color:** 6 brown axial markings on black

**Electrically conductive:**  $R < 10^6 \Omega/m$

### Applications

for conveying benzine, mineral oil, gasoil, kerosene, fuel oil, motor oil, compressed air, cold/hot water with or without detergents, vegetable oils, animal fats, propane, butane, diluted acids, technical alcohols, pesticides, ...

Reference	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Bending radius (mm)	Coil length (m)
F-UX6006	6 x 13	160	20	60	35	50
F-UX6008	8 x 15,5	210	20	60	50	50
F-UX6010	10 x 17,5	250	20	60	60	50
F-UX6013	13 x 21	320	20	60	80	50
F-UX6016	16 x 25	430	20	60	100	50
F-UX6019	19 x 29	550	20	60	120	50
F-UX6025	25 x 36	760	20	60	150	50

Product ID: 40406

Source URL: <http://articom.be/en/products/40000/40400/unitrix-60-0>