

Panneaux



Qualité standard bleutée transparent

Dureté 75°ShA

Température: -20°C à +50°C

Largueur x Ep (mm)	Poids (g/m)	Référence	Courronage (m)
1000 x 1	1250	LC10001	20
1000 x 2	2500	LC10002	20
1000 x 3	3750	LC10003	20
1000 x 4	5000	LC10004	20
1000 x 5	6250	LC10005	20
1000 x 6	7500	LC10006	20
1000 x 7	8750	LC10007	20
1000 x 8	10000	LC10008	20
1000 x 10	12500	LC10010	20
1200 x 1	1500	LC12001	20
1200 x 2	3000	LC12002	20
1200 x 3	4500	LC12003	20
1200 x 4	6000	LC12004	20
1200 x 5	7500	LC12005	20
1200 x 6	9000	LC12006	20
1200 x 7	10500	LC12007	20
1200 x 8	12000	LC12008	20
1500 x 2	3750	LC15002	20
1500 x 3	5630	LC15003	20
1500 x 4	7500	LC15004	20
1500 x 5	9380	LC15005	20
1500 x 6	11250	LC15006	20
1500 x 7	13130	LC15007	20
1800 x 3	6750	LC18003	20
1800 x 4	9000	LC18004	20
1800 x 5	11250	LC18005	20
2200 x 3	8250	LC22003	20
2200 x 4	11000	LC22004	20
2200 x 5	13750	LC22005	20
2200 x 7	19250	LC22007	20

Product ID: 22000

URL source: <http://articom.be/fr/products/20000/platen-0>