

AX EPDM 10 bar

Delivery hose of highly aggressive chemical products, organic and non organic acids in high concentration, slats, bases, ketones and dye products for cloth industry.

- **Tube:** black smooth and anti static EPDM
- **Reinforcement:** high strength synthetic cord and anti-static copper wire to facilitate the electrical connection
- **Cover:** black CR with cloth impression, anti-static ($R < 10^6 \Omega/m$), weathering, ozone and chemical products resistant

Temperature range: -40°C up to +90°C (depending on medium and concentration)

Note: NOT suitable for hydrocarbons

Cleaning with hot water or steam (120°C)

Applications

See chemical resistance chart for details. For acids, bases and solvents at temperature exceeding 25°C (+77°F) please contact us.

Diameter (mm)	Weight (g/m)	WP bar)	BP (bar)	Ref	Coil length (m)
13 x 23	360	10	30	F-EPDMSS013	40 - 60
19 x 29	440	10	30	F-EPDMSS019	40 - 60
20 x 35	460	10	30	F-EPDMSS020	40 - 60
25 x 35	550	10	30	F-EPDMSS025	40 - 60
30 x 42	850	10	30	F-EPDMSS030	40 - 60
32 x 44	890	10	30	F-EPDMSS032	40 - 60
35 x 47	1.050	10	30	F-EPDMSS035	40 - 60
38 x 52	1.210	10	30	F-EPDMSS038	40 - 60
40 x 55	1.410	10	30	F-EPDMSS040	40 - 60
51 x 66	1.810	10	30	F-EPDMSS050	40 - 60
60 x 76	2.080	10	30	F-EPDMSS060	40 - 60
80 x 96	2.770	10	30	F-EPDMSS080	40 - 60
102 x 118	3.600	10	30	F-EPDMSS100	40 - 60

Product ID: 40212

Source URL: <https://articom.be/en/products/40000/40200/ax-epdm-10-bar-0>