

Filclair N



Flexible and polyvalent reinforced pvc hose; suitable for a large number of media: industrial gasses or liquids. Filclair can be used in vacuum up to Ø25mm.

Temperature: -15°C to +60°C

- **Tube:** transparant pvc
- **Reinforcement:** high tensile textile thread
- **Cover:** transparant pvc

Attention: not suitable for hydrocarbons and derivatives

On demand also available in different colours.

Applications

supply of compressed air for machinery
industrial gases and liquids
light chemical products

Assembly

All types of industrial couplings
assembly with hose-clamps

Reference	Diameter (mm)	Bending radius (mm)	Weight (g/m)	Working Pressure (bar)	Burst Pressure (bar)	Coil length (m)
FC0408	4 x 8	40	49	10	30	50
FC0508	5 x 8	40	39	10	30	50
FC0611	6,3 x 11	50	82	10	30	50
FC0612	6 x 12	55	110	15	50	50
FC0813	8 x 13	65	105	10	30	50
FC0814	8 x 14	60	130	15	50	50
FC0915	9 x 15	65	141	15	50	50
FC1015	10 x 15	85	131	10	30	50
FC1016	10 x 16	75	155	15	50	50
FC1218	12 x 18	105	170	10	30	50
FC1319	13 x 19	90	192	15	50	50
FC1320	13 x 20	90	225	15	50	50
FC1521*	15 x 21	145	216	10	30	50
FC1622	16 x 22	155	222	10	30	50
FC1926	19 x 26	195	302	10	30	50
FC2533	25 x 33	235	432	10	30	50
FC3242*	32 x 42	185	716	12	38	25 - 50
FC3848*	38 x 48	220	865	10	32	25
FC5060	50 x 60	390	1072	8	24	25

Product ID: 12080

Source URL: <https://articom.be/en/products/10000/12000/filclair-n-0>