

Amazon SE



Professional super elastic (SE) pvc spiral hose, for the suction and delivery of used water. Specially constructed to meet the demands of cleaning trucks. Easy to use, even at low temperatures.

Temperature: -20°C to +60°C

Constructie: plasticized grey pvc, reinforced by a concealed white hard pvc spiral, very flexible and smooth on both in- and outside

Security coefficient at 20°C: 3 times the WP

Applications

Suction and discharge for used water

Assembly

all types of couplings, assembled with hose clamps

Reference	Diameter (mm)	Wall thickness (mm)	Weight (g/m)	Bending radius (mm)	Working Pressure (bar)	Vacuum (mH2O)	Coil length (m)
APSE020	20	3,5	300	125	6	10	50
APSE025	25	3,7	400	130	6	10	50
APSE030	30	3,7	550	140	6	10	50
APSE032	32	4	610	145	6	10	50
APSE035	35	4,2	630	150	6	10	50
APSE038	38	4,3	690	175	6	10	50
APSE040	40	4,4	720	185	6	10	50
APSE045	45	4,5	860	200	5,5	10	50
APSE050	50	4,6	1000	235	5	10	50
APSE055	55	4,8	1150	250	5	9	50
APSE060	60	5	1260	280	5	9	50
APSE063	63	5,2	1400	300	4,5	9	50
APSE070	70	5,4	1600	340	4,5	9	50
APSE076	76	5,5	1720	375	4,5	9	50
APSE080	80	6	1860	400	4	9	50
APSE090	90	6,3	2100	440	4	9	50
APSE102	102	6,6	2700	490	3,5	8	30 - 50
APSE110	110	6,9	2950	550	3,5	8	30
APSE120	120	7,5	3400	610	3	8	25
APSE125	125	7,5	3650	650	3	8	20
APSE150	150	8,8	5100	780	2	8	20
APSE200	200	12	9600	1160	1,5	8	10
APSEGB063	63	5,2	1400	300	4,5	9	50
	75	5,5	1720	375	4,5	9	50
APSEGB075	90	6,3	2100	440	4	9	50

APSEGB090	100	6,6	2700	490	3,5	8	50
APSEGB100	125	7,5	3650	650	3	8	4 - 5 - 50
APSEGB125	150	8,8	5100	780	2	8	4 - 5 - 50
APSEGB150	200	12	9600	1160	1,5	8	10
APSEGB200							

Product ID: 14030

Source URL: <https://articom.be/en/products/10000/14000/amazone-se-0>