

TU25



Flexible delivery multi-purpose hose suitable for industrial oils, unleaded fuels (EN228:2008), diesel (EN590:2010) and heating oils (DIN 51 603 parts 1.5)

Temperature: -25°C to +90°C

- **Tube:** black smooth and electrically conductive NBR
- **Reinforcement:** textile spiral construction
- **Cover:** smooth NBR/SBR abrasion resistant, isolating, weather resistant and oil resistant.
- **Color:** black with 3 axial red lines

Electrically conductive: $R < 10^6 \Omega/m$

Applications

Industry, garages, filling stations and vehicle repair shops

ATTENTION: Not to be used as a petrol pump hose!

Assembly

Reference	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Bending radius (mm)	Coil length (m)
F-MS006013	6 x 13	150	25	75	40	50
F-MS008016	8 x 16	220	25	75	50	50
F-MS010018	10 x 18	250	25	75	60	50
F-MS013021	13 x 21	300	25	75	80	50
F-MS016025	16 x 25	400	25	75	100	50
F-MS019029	19 x 29	530	25	75	120	50
F-MS025036	25 x 36	720	25	75	150	50

Product ID: 40402

Source URL: <https://articom.be/en/products/40000/40400/tu25-0>