


UNITRIX 80



The multi purpose hose UNITRIX 80® provides best results when used in the areas of mechanical engineering, farming, forestry, garages, quarries, construction sites, shipbuilding, railway industry, mineral oil, chemical, and petrochemical industry.

Temperature: -25°C to +85°C It can be used with compressors, barrel pumps and aggregates.

- **Inner tube:** black, non-porous smooth NBR lining
- **Reinforcements:** synthetic fibres
- **Cover:** NBR, resistant to oil, grease and chemicals
- **Color:** 6 olive green axial markings on black

Electrically conductive: $R < 10^6 \Omega/m$

Applications

for conveying benzine, mineral oil, gasoil, kerosene, fuel oil, motor oil, compressed air, cold/hot water with or without detergents, vegetable oils, animal fats, propane, butane, diluted acids, technical alcohols, pesticides, ...

Reference	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Bending radius (mm)	Coil length (m)
F-UX8006	6 x 14	190	33	80	35	50
F-UX8008	8 x 16	230	33	80	50	50
F-UX8010	10 x 18	260	33	80	60	50
F-UX8013	13 x 21	370	33	80	80	50
F-UX8016	16 x 26	480	33	80	100	50
F-UX8019	19 x 31	680	33	80	120	50
F-UX8025	25 x 37	840	33	80	150	50
F-UX8032	32 x 44	935	33	80	150	40
F-UX8038	38 x 51	1.150	33	80	190	40
F-UX8050	50 x 64	1.610	33	80	250	40
F-UX8060	60 x 78	2.260	33	80	400	40
F-UX8075	75 x 93	3.050	33	80	500	40

Product ID: 40408

Source URL: <https://articom.be/en/products/40000/40400/unitrix-80-0>