

junction coupling



Guillemin junction coupling with locking rings on each side.

Available in Aluminium, Stainless Steel, Brass or Polypropylene

Working Pressure: 16 bar

Standard with NBR seal

(ND = nominal diameter)

ND	Inch	Ref Alu	Ref SS	Ref Brass	Ref PP
20 > 40	3/4 > 1" 1/2	GUR020040	GUIR020040	GUBR020040	-
30 > 40	1" 1/4" > 1" 1/2	GUR030040	GUIR030040	GUBR030040	-
40 > 50	1" 1/2 > 2"	GUR040050	GUIR040050	GUBR040050	-
40 > 65	1" 1/2 > 2" 1/2	GUR040065	GUIR040065	GUBR040065	-
40 > 80	1" 1/2 > 3"	GUR040080	GUIR040080	GUBR040080	-
40 > 100	1" 1/2 > 4"	GUR040100	GUIR040100	GUBR040100	-
50 > 65	2" > 2" 1/2	GUR050065	GUIR050065	GUBR050065	-
50 > 80	2" > 3"	GUR050080	GUIR050080	GUBR050080	GUPR04080
50 > 100	2" > 4"	GUR050100	GUIR050100	GUBR050100	-
65 > 80	2" 1/2 > 3"	GUR065080	GUIR065080	GUBR065080	-
65 > 100	2" 1/2 > 4"	GUR065100	GUIR065100	GUBR065100	-
80 > 100	3" > 4"	GUR080100	GUIR080100	GUBR080100	-

Product ID: 90140

Source URL: <https://articom.be/en/products/90000/90001/90100/guillemin-reductie-koppeling-0>