

Storz with shank



Storz half-coupling with hose shank.

Lug distances(1): D = 31 , C = 66 , B = 89 , A = 133

Alloys: aluminium or Stainless Steel(2).

Profiled seal: NBR

Working pressure: 16 bar (ND205: 10bar)

(1) Most common, other available (see table)

(2) Please contact us

ND	Inch	For hose (mm)	Lug dist. (mm)	DIN	Ref Alu
25	1"	25	31	14 301	SZT031025
32	3/4"	19	44		SZT044019
32	1"	25	44		SZT044025
32	1" 1/4	32	44		SZT044032
38	1" 1/2	38	51		SZT052038
52	1"	25	66		SZT066025
52	1" 1/4	32	66		SZT066032
52	1" 1/2	38	66		SZT066038
52	2"	52	66	14 321	SZT066052
52		60	66		SZT066060
65	2"	52	81		SZT081052
65	2" 1/2	65	81		SZT081065
65		70	81		SZT081070
75	2"	52	89		SZT089052
75	2" 1/2	65	89	14 322	SZT089065
75	3"	75	89		SZT089075
75		80	89		SZT089080
90		90	105		SZT105090
100	4"	100	115		SZT115100
110		90	133		SZT133090
110	4"	100	133		SZT133100
110		110	133	14 323	SZT133110
125	5"	125	148		SZT148125
150	6"	150	160		SZT160150
205		205	220		SZT220205

Product ID: 90810

Source URL: <https://articom.be/en/products/90000/90001/90800/storz-met-tule-0>