

Storz female threaded



Storz half-coupling with female thread. Available with fixed head or swivel.

Lug distances(1): D = 31 , C = 66 , B = 89 , A = 133

Thread: BSP, DIN ISO 228

Alloys: aluminium or Stainless Steel(2).

Profiled seal: NBR

Working pressure: 16 bar (ND205: 10bar)

(1) Most common, other available (see table)

(2) Please contact us

ND	Inch	Lug dist. (mm)	DIN	Ref	Ref Swivel
25	1"	31	14 306	SZV031025	
32	1"	44		SZV032025	
32	1" 1/4	44		SZV044032	
38	1"	51		SZV052025	
38	1" 1/4	51	14 307	SZV052032	
38	1" 1/2	51		SZV052038	
38	2"	51		SZV052050	
52	1"	66		SZV066025	
52	1" 1/4	66	14 308	SZV066032	
52	1" 1/2	66		SZV066038	SZVD066038
52	2"	66		SZV066050	SZVD066050
52	2" 1/2	66		SZV066065	
65	2"	81	14 309	SZV081050	
65	2" 1/2	81		SZV081065	
65	3"	81		SZV081075	
75	2"	89		SZV089050	
75	2" 1/2	89	14 308	SZV089065	SZVD089065
75	3"	89		SZV089075	SZVD089075
90	3"	105		SZV105075	
100	4"	115		SZV115100	SZVD115100
100	4"	133	14 309	SZV133100	SZVD133100
110	4" 1/2	133		SZV133110	
125	5"	148		SZV148125	SZVD148125
150	6"	160		SZV160150	SZVD160150
165	6"	188		SZV188150	
250	10"	278		SZV278250	

Product ID: 90820

Source URL: <https://articom.be/en/products/90000/90001/90800/storz-met-vrouw-draad-0>